□□ v10 kylin v10 □□ firewall□□□□□□

□□□□□□□□□□□□□□

> □ `firewall-cmd --reset-default-zone` □ firewalld □□□□□□□□□□

□□□□□□□□□□□□□□□□□□

□□ □□□□□□□□

□□ `public zone` □□□□

```
sources: 10.2.2.0/24   ← □□
ports: □□□□□□
masquerade: no
```

□□□

□ □□□□ “□□□ ”

□□□

> ⚠ zone □□□□□□□□□ reset □□□□

□□ □□ “□□□□□ ”□□□ Kylin V10 □□□

□ □□ 1□□□□□□ zone + □□□□□

1□ □□□ ports

```
for p in 80 443 8070 20881 8082 20853 8086 20835 4443; do
  firewall-cmd --permanent --zone=public --remove-port=${p}/tcp
done
```

2□ □□ source□□□

□□□□□

```
sources: 10.2.2.0/24
```

□□□

```
firewall-cmd --permanent --zone=public --remove-source=10.2.2.0/24
```

3□ □□ ssh / □□□

```
firewall-cmd --permanent --zone=public --add-service=ssh
```

4□ reload

```
firewall-cmd --reload
```

□ □□ 2□□□□□□□

public zone □□□

□□□□ “□□□□□□□ ”□□□□□

```
systemctl stop firewalld

rm -f /etc/firewalld/zones/public.xml

systemctl start firewalld
```

□□ □□□ firewalld □□□□□□ public zone

□□ □□ 3

□□□□□□□□□□□□

firewalld

```
systemctl stop firewalld
rm -rf /etc/firewalld
yum reinstall firewalld -y   # □ dnf
systemctl start firewalld
```

□□ □□□□□□ “□□□□□□ ”□

⚠ □□□□□□□□□□□□

```
sources: 10.2.2.0/24
```

□□□□□

> “□□ □ firewall □□□□□ “□□□□□□□□ ”

□□□□□□□

- □□□□□□
- □□□□□□□
- Docker + firewalld □□

□□ □□□□□

□□	□□□□
reset-default-zone	□ □□□
remove-port + reload	✔ □□□□
□□ zone XML	✔ □□
□□ firewalld	✔ □□□

□□

□□□□□□□□□□□□□

□□□□□□□□□

□□ □□□□□□□

```
rm -f /etc/firewalld/zones/public.xml
systemctl restart firewalld
```

□□□□□□□□

- ssh
- □□□□□　　80/443

□□□□□□□□□□□□□□□□

> “□□　V10 + Docker + □□□□

□□□□□□

✔ □□□□□
✔ DOCKER-USER □□□□
✔ firewalld □□□□□□
✔ □□□□□　　“□□□□　　/ □□□□　　”

□□□□□□□□□□□□

Revision #1
Created 2026-05-12 07:32:43 UTC by Admin
Updated 2026-05-12 07:33:24 UTC by Admin