

# Docker????????

#### docker[]

docker save -o xampp\_7.tar ef5954c4d0d1

#####

docker load -i xampp\_7.tar

####

docker tag c1b6ba59135e amazoncorretto:8u352-alpine3.16-tini

#####

docker commit <container\_name\_or\_id> <new\_image\_name>:<tag>

1. []

docker-compose down

2. []

[] docker-compose #####

docker-compose config | awk '/image:/{print \$2}' | xargs -I {} docker save -o {}.tar {}

[] docker-compose.yml ##### .tar []

3. #####

#####

#####

docker volume ls

##### my\_volume[]

docker run --rm -v my\_volume:/volume -v \$(pwd):/backup busybox tar czf /backup/my\_volume.tar.gz -C /volume .

4. [] tar.gz

##### tar.gz []

tar czf docker\_backup.tar.gz \*.tar \*.tar.gz

#####




[] docker\_backup.tar.gz ##### scp #####

scp docker\_backup.tar.gz user@target\_server:/path/to/destination

#####

```
1. tar.gz
docker_backup.tar.gz
```

```
tar xzf docker_backup.tar.gz
```

2.   
 Docker 

```
for image in *.tar; do docker load -i $image; done
```

```
docker load -i mongodb:24.8.9.1.tar &&\ndocker load -i mysql:24.8.2.tar &&\ndocker load -i rabbitmq:24.8.2.tar &&\ndocker load -i redis:3.2.2.tar &&\ndocker load -i szdriver:24.8.9.7.tar &&\ndocker load -i javaapp:24.8.9.2.tar
```

[illegible]

```
docker run --rm -v my_volume:/volume -v $(pwd):/backup busybox tar xzf /backup/my_volume.tar.gz -C /volume
```

[illegible]

```
docker-compose up -d
```

Revision #1

Created 14 May 2025 06:12:39 by Admin

Updated 14 May 2025 06:12:57 by Admin