

Mysql?????????

1[] log_bin[] skip-log-bin []

2[] [mysqld]

a[]

vi /etc/my.cnf

server-id = 1

log-bin = /home/shuncom/mysql/data/mysql-bin

binlog_cache_size = 4M

binlog_format = mixed

max_binlog_cache_size = 8M

max_binlog_size = 512M

expire_logs_days = 14

gtid_mode = ON

enforce_gtid_consistency = ON

[] mysql[]

systemctl restart mysqld.service

b[]

vi /etc/my.cnf

server-id = 2

slave-skip-errors=1007,1022,1050,1062,1169

relay-log=/home/shuncom/mysql/data/relay-log

max_relay_log_size=512M

relay-log-purge=ON

read-only

gtid_mode = ON

enforce_gtid_consistency = ON

[] mysql[]

systemctl restart mysqld.service

3[]

a[] root[]

mysql -u root -p'Sz_clighting'

b[]

CREATE USER 'replicator'@'%' IDENTIFIED BY 'Passw0rd';

```
GRANT REPLICATION SLAVE ON *.* TO 'replicator'@'%';  
FLUSH PRIVILEGES;  
SHOW MASTER STATUS\G; --  MASTER_LOG_FILE  MASTER_LOG_POS
```

```
4
```

```
a  root
```

```
mysql -u root -p'Sz_clighting'
```

```
b
```

```
CHANGE MASTER TO  
MASTER_HOST='172.17.20.17',  
MASTER_PORT=3306,  
MASTER_USER='replicator',  
MASTER_PASSWORD='Passw0rd',  
MASTER_LOG_FILE='mysql-bin.000001',  
MASTER_LOG_POS=868,  
get_master_public_key=1;
```

```
CHANGE MASTER TO MASTER_DELAY = 3600;  
START SLAVE;  
SHOW SLAVE STATUS\G;
```

Revision #1

Created 14 May 2025 05:57:45 by Admin

Updated 14 May 2025 05:58:21 by Admin